



Unicable II™

19W Power Supply adapter for Unicable II™ multiswitches (UK plug)

IDLU-ADPT01-19W00-UPM

Item: 5638

This power supply adapter is designed to power up a single 4-output Unicable II™ multiswitch and a connected Quattro LNB (or two wideband LNBs) over the DC input port or over the trunk lines. It features over current and short circuit protections and a built-in fuse protecting against power line surges and abnormal conditions making it ideal for building/MDU installations of cascaded systems.

Technical Specifications

Input voltage	100 VAC ~ 240 VAC
Input frequency	50 Hz/60 Hz
Output voltage	19 V
Output current	1 A
Output power	19.0 W
Average efficiency	86.8 % min. (230 Vac)
Efficiency at low load (10%)	79.9 % (230 Vac)
No-load power consumption	0.075 W max.
Output connector	F-type (male)
Cable length (AC)	Wall plug
Cable length (DC)	1.5 m
Product dimensions (L x W x H)	77 mm x 45 mm x 70 mm
Working temperature	0 °C ~ +40 °C
Weight	123 g

Logistical information

Packaging dimensions (h x w x d)	25cm x 12 cm PE bag
Packaging weight	0.125 Kg
Quantity per carton	72
Carton dimensions (h x w x d)	45 cm x 39 cm x 33.5 cm
Carton weight	1.5 Kg
Quantity per pallet	1728 pcs